

We're Different

With 6 years+ of research and 15 patents, Illumisoft has developed completely new types of light fixtures. Using hi-tech optical film lenses, reflectors and innovative fixture designs, a new standard has been achieved for extraordinary light quality, energy efficiency, and value.

World's #1 Rated Most Energy Efficient

Our ratings say it all.
Out 6400 retrofit products in-class:
The top 4 listings
6 out of the top 10
34 out of the top 50

Light Quality Is Our Passion

With an industry wide race to deliver light at a lower cost, light quality has been virtually forgotten. We believe superior light quality can enhance people's lives. Soft, indirect **low-glare** light that makes people feel good is our focus.





96% Efficient Low Glare Light Shaping Optical Film Lenses

Soft Indirect Low Glare Light With Fully Luminous Aperture

Light-Weight All Aluminum
Construction 5.8 lbs. (2x2)
Long Rust-Free Durability

Advanced Thermal Management For Long LED Life

Removable Electronics Module For Easy Upgrade or Repair

97% Efficient Internal
Optical Film Reflectors and End Panels





34 OUT OF THE TOP 50

П

RETROFIT REFINED Retrofits are now no longer limited to center baskets and flat panels. With the same architectural artistry merged with soft diffused indirect light as the V Series, it's the #1 rated energy saving retrofit fixture on DLC. Up to 167 lumens/watt delivered. Custom sizes to fit nearly any troffer. **OUR ENERGY SAVINGS RANKING** About a five minute installation. **OUT 6400 PRODUCTS IN-CLASS: TOP 4 LISTINGS** 6 OUT OF THE TOP 10



ORDERING GUIDE

Model	EW DM	Ecowing Dimensions
Series	R V	Retrofit New Construction/Remodel
Width	12 20 24	12" 20" (Ecowing-R only) 24"
Length	24 48	24" 48"
Wattage	Chosen Lumen Ou	ll Be Determined By tput And Color Temp. t For Approx. Wattages
Driver Mounting	I WE BC	Integral – V Series Only Wiring Enclosure – R Series Only Ballast Cover Re-Use – R Series Only
Nominal Lumens	26L 32L 35L 42L 50L 55L	2600 lm 3200 lm 3500 lm 4200 lm 5000 lm 55000 lm
CCT	CT30 CT35 CT41 CT50	3000k (option) 3500k 4100k 5000k
Control	D	Standard Dimming (0-10V, PWM, Trim Pot)
Voltage	120 347	100 - 277 V 100 - 347 V
Options	X EBB DR MS CRI	No Options Emergency Battery Backup Driver Upgrade Master/Satellite Wiring 95 Cri With 95% R9
All Las Caria	a a sac a su dible asserta	

All Eco Series come with quick change plug and play driver modules for quick and easy upgrades.



ECOWING-R

DIMENSIONS

FILMTECH

Our optical film technology (15 patents) utilizes 96% transmissive lens film with micro-structured surfaces which are able to control and direct light. This creates highly diffused light that also has low glare. Our reflection film further spreads and diffuses light with 98% efficiency. Together they create soft low glare fully lit apertures with a visually comfortable, quiet appearance.



















Canadian Sales:

cdnsales@illumisoftlighting.com 888-441-0555 Press #1



USA Sales:

usasales@illumisoftlighting.com 888-441-0555 Press #2



160 Spruce St. Ottawa ON K1R 1C6 www.illumisoftlighting.com

IL-ES-BR 02/19 Copyright © 2019 Illumisoft Lighting Canada Ltd. All rights reserved.

Please refer to online specifications for most up-to-date content as specifications are subject to change without notice.