

ORDERING GUIDE

FEATURES	CODE	OPTIONS	DESCRIPTION
Model	<input type="text"/>	WTF	Eco-WTF
Series	<input type="text"/>	R	Fixture-In-Fixture Retrofit
Width	<input type="text"/>	24	24"
Length	<input type="text"/>	24 48	24" 48"
Wattage	<input type="text"/>		See models chart.
Driver Mounting	<input type="text"/>	WE BC	Wiring Enclosure Re-use existing ballast cover
Nominal Lumens	<input type="text"/>	32L 42L	3200 lm 4200 lm
CCT	<input type="text"/>	CT30 CT35 CT41 CT50	3000k (option) 3500k 4100k 5000k
Control	<input type="text"/>	D	Standard Dim (0-10V, PWM, Trim Pot)
Voltage	<input type="text"/>	120 347	100 - 277 V 100 - 347 V
Options	<input type="text"/>	X SH DR MS CRI	No Options Safety Harness Driver Upgrade Master/Satellite Wiring 95 Cri With 95% R9

Consult your sales representative for lead times.

MODELS

MODEL	NOM. LUMENS	LM/W	WATTS	CCT
WTF-24-48-30W-XX-42L-CT35-D-120-XXXX	4200	140.02	30.00	3500
WTF-24-48-29W-XX-42L-CT41-D-120-XXXX	4200	147.03	28.57	4100
WTF-24-48-28W-XX-42L-CT50-D-120-XXXX	4200	154.05	27.26	5000
WTF-24-24-24W-XX-32L-CT35-D-120-XXXX	3200	131.79	24.28	3500
WTF-24-24-23W-XX-32L-CT41-D-120-XXXX	3200	138.44	23.11	4100
WTF-24-24-22W-XX-32L-CT50-D-120-XXXX	3200	145.09	22.06	5000
WTF-24-48-30W-XX-42L-CT35-D-347-XXXX	4200	140.02	30.00	3500
WTF-24-48-29W-XX-42L-CT41-D-347-XXXX	4200	147.03	28.57	4100
WTF-24-48-28W-XX-42L-CT50-D-347-XXXX	4200	154.05	27.26	5000
WTF-24-24-24W-XX-32L-CT35-D-347-XXXX	3200	131.79	24.28	3500
WTF-24-24-23W-XX-32L-CT41-D-347-XXXX	3200	138.44	23.11	4100
WTF-24-24-22W-XX-32L-CT50-D-347-XXXX	3200	145.09	22.06	5000

2x2 Dimensions: 21.25" W x 21.9375" L x 2.65" D

2x4 Dimensions: 21.25" W x 45.9375" L x 2.65" D

Weight - 2.5 lbs. 2x2, 4.5 lbs. 2x4

Canadian Sales: cdnsales@illumisoftlighting.com 888-441-0555 Press #1 

USA Sales: usasales@illumisoftlighting.com 888-441-0555 Press #2 