

ORDERING GUIDE


FEATURES	CODE	OPTIONS	DESCRIPTION
Model	<input type="text"/>	EW	Ecowing
Series	<input type="text"/>	R	Fixture-In-Fixture Retrofit
Width	<input type="text"/>	12 20 24	12" 20" 24"
Length	<input type="text"/>	24 48	24" 48"
Wattage	<input type="text"/>		See models chart.
Driver Mounting	<input type="text"/>	WE BC	Wiring Enclosure Re-use existing ballast cover
Nominal Lumens	<input type="text"/>	26L 32L 42L 50L	2600 lm 3200 lm 4200 lm 5000 lm Please see compatibility note. Custom tuned outputs up to 5500 lm available on request.
CCT	<input type="text"/>	CT30 CT35 CT41 CT50	3000k (option) 3500k 4100k 5000k
Control	<input type="text"/>	D	Standard Dim (0-10V, PWM, Trim Pot)
Voltage	<input type="text"/>	120 347	100 - 277 V 100 - 347 V
Options	<input type="text"/>	X SH EBB DR MS CRI	No Options Safety Harness Emergency Battery Backup Driver Upgrade Master/Satellite Wiring 95 Cri With 95% R9

ECOWING-R	2600L	3200L	3500L	4200L	5000L	5500L
2x4		☑		☑	☑	
2x2	☑	☑		☑		
20"x48"				☑	☑	
1x4		☑		☑	☑	

Consult your sales representative for lead times.

MODELS

MODEL	NOM. LUMENS	LM/W	WATTS	CCT
EW-24-48-37W-XX-50L-CT35-D-120-XXXX	5000	139	37	3500
EW-24-48-34W-XX-50L-CT41-D-120-XXXX	5000	147	34	4100
EW-24-48-33W-XX-50L-CT50-D-120-XXXX	5000	153	33	5000
EW-24-48-29W-XX-42L-CT35-D-120-XXXX	4200	144	29	3500
EW-24-48-28W-XX-42L-CT41-D-120-XXXX	4200	152	28	4100
EW-24-48-27W-XX-42L-CT50-D-120-XXXX	4200	158	27	5000
EW-24-24-29W-XX-42L-CT41-D-120-XXXX	4200	143	29	4100
EW-24-24-28W-XX-42L-CT50-D-120-XXXX	4200	149	28	5000
EW-24-24-22W-XX-32L-CT35-D-120-XXXX	3200	143	22	3500
EW-24-24-21W-XX-32L-CT41-D-120-XXXX	3200	150	21	4100
EW-24-24-21W-XX-32L-CT50-D-120-XXXX	3200	156	21	5000
EW-24-24-17W-XX-26L-CT35-D-120-XXXX	2600	154	17	3500
EW-24-24-16W-XX-26L-CT41-D-120-XXXX	2600	161	16	4100
EW-24-24-16W-XX-26L-CT50-D-120-XXXX	2600	167	16	5000
EW-20-48-37W-XX-50L-CT35-D-120-XXXX	5000	139	37	3500
EW-20-48-34W-XX-50L-CT41-D-120-XXXX	5000	147	34	4100
EW-20-48-33W-XX-50L-CT50-D-120-XXXX	5000	153	33	5000
EW-20-48-29W-XX-42L-CT35-D-120-XXXX	4200	144	29	3500
EW-20-48-28W-XX-42L-CT41-D-120-XXXX	4200	152	28	4100
EW-20-48-27W-XX-42L-CT50-D-120-XXXX	4200	158	27	5000
EW-12-48-37W-XX-50L-CT35-D-120-XXXX	5080	138	37	3500
EW-12-48-36W-XX-50L-CT35-D-120-XXXX	5000	138	36	3500
EW-12-48-34W-XX-50L-CT41-D-120-XXXX	5000	145	34	4100
EW-12-48-33W-XX-50L-CT50-D-120-XXXX	5000	152	33	5000
EW-12-48-29W-XX-42L-CT35-D-120-XXXX	4200	143	29	3500
EW-12-48-28W-XX-42L-CT41-D-120-XXXX	4200	150	28	4100
EW-12-48-27W-XX-42L-CT50-D-120-XXXX	4200	156	27	5000
EW-12-48-22W-XX-32L-CT35-D-120-XXXX	3200	148	22	3500
EW-12-48-21W-XX-32L-CT41-D-120-XXXX	3200	155	21	4100
EW-12-48-20W-XX-32L-CT50-D-120-XXXX	3200	162	20	5000
EW-24-48-37W-XX-50L-CT35-D-347-XXXX	5000	139	37	3500
EW-24-48-34W-XX-50L-CT41-D-347-XXXX	5000	147	34	4100
EW-24-48-33W-XX-50L-CT50-D-347-XXXX	5000	153	33	5000
EW-24-48-29W-XX-42L-CT35-D-347-XXXX	4200	144	29	3500
EW-24-48-28W-XX-42L-CT41-D-347-XXXX	4200	152	28	4100
EW-24-48-27W-XX-42L-CT50-D-347-XXXX	4200	158	27	5000
EW-24-24-22W-XX-32L-CT35-D-347-XXXX	3200	143	22	3500
EW-24-24-21W-XX-32L-CT41-D-347-XXXX	3200	150	21	4100
EW-24-24-21W-XX-32L-CT50-D-347-XXXX	3200	156	21	5000
EW-24-24-29W-XX-42L-CT41-D-347-XXXX	4200	143	29	4100
EW-24-24-28W-XX-42L-CT50-D-347-XXXX	4200	149	28	5000
EW-20-48-37W-XX-50L-CT35-D-347-XXXX	5000	139	37	3500
EW-20-48-34W-XX-50L-CT41-D-347-XXXX	5000	147	34	4100
EW-20-48-33W-XX-50L-CT50-D-347-XXXX	5000	153	33	5000
EW-20-48-29W-XX-42L-CT35-D-347-XXXX	4200	144	29	3500
EW-20-48-28W-XX-42L-CT41-D-347-XXXX	4200	152	28	4100
EW-20-48-27W-XX-42L-CT50-D-347-XXXX	4200	158	27	5000
EW-12-48-37W-XX-50L-CT35-D-347-XXXX	5080	138	37	3500
EW-12-48-36W-XX-50L-CT35-D-347-XXXX	5000	138	36	3500
EW-12-48-34W-XX-50L-CT41-D-347-XXXX	5000	145	34	4100
EW-12-48-33W-XX-50L-CT50-D-347-XXXX	5000	152	33	5000
EW-12-48-29W-XX-42L-CT35-D-347-XXXX	4200	143	29	3500
EW-12-48-28W-XX-42L-CT41-D-347-XXXX	4200	150	28	4100
EW-12-48-27W-XX-42L-CT50-D-347-XXXX	4200	156	27	5000
EW-12-48-22W-XX-32L-CT35-D-347-XXXX	3200	148	22	3500
EW-12-48-21W-XX-32L-CT41-D-347-XXXX	3200	155	21	4100
EW-12-48-20W-XX-32L-CT50-D-347-XXXX	3200	162	20	5000



Format	Faceplate Width B	Faceplate Length A	Depth C
4' Length	9" to 21.25"	45.9375"	2.625"
2' Length	9" to 21.25"	21.9375"	2.625"

Canadian Sales: cdnsales@illumisoftlighting.com 888-441-0555 Press #1 

USA Sales: usasales@illumisoftlighting.com 888-441-0555 Press #2 

IL-EWV-DS- 06/19